

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001259 A1

(51) International Patent Classification⁷: **F16J 15/34**,
G01M 13/00

(74) Agent: GARAVELLI, Paolo; A.Bre.Mar. S.r.l., Via Ser-
vais, 27, I-10146 Torino (IT).

(21) International Application Number:
PCT/IT2003/000154

(22) International Filing Date: 13 March 2003 (13.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2002A001396 25 June 2002 (25.06.2002) IT

(71) Applicant (for all designated States except US): TER-
MOELETTRONICA S.P.A. [IT/IT]; Via Petrarca 10,
I-24052 Azzano S. Paolo (IT).

(72) Inventor; and


(75) Inventor/Applicant (for US only): COMPER, Riccardo
[IT/IT]; Via Petrarca 10, I-24052 Azzano S. Paolo (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MULTIFUNCTIONAL ELECTRONIC DEVICE FOR A MECHANICAL SEAL AND CONTROL AND MANAGE-
MENT PROCESS REALISED BY SUCH DEVICE



(57) Abstract: Multifunctional electronic device (30) based on a microprocessor for checking and managing all operating and diagnostic conditions of a mechanical seal (10, 20). A mechanical seal, installed on pumps or process machines (11, 21), comprises two coupled surfaces, one rotating and integral with a shaft and one stationary and integral with the or machine in which the shaft is inserted; these two surfaces are kept in contact through combined forces: a mechanical force generated by springs and another hydraulic force generated by the pressure of a fluid and suitably controlled by a pressure regulator (103, 202, 302). The electronic device regulates the pressurization of a mechanical seal to variable pressure values, keeping the optimum difference (305) constant between pressure (303) inside the mechanical seal and pressure (304) in the pump delivery line or inside the process machine in which the seal is installed.

WO 2004/001259 A1